# Material Safety Data Sheet

May be used to comply with

OSHA's Hazard Communication Standard, 29 CFR 1910.1200

Standard must be consulted for specific requirements.

# U.S. Department of Labor

Occupational Safety and Health Administration (Non-Mandatory Form)

Form Approved OMB No. 1218-0072

IDENTITY (As Used on Label and List) Oil Based Block Printing Ink (3450-3460, 3550-3556)	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
Section I Manufacturer's Name Speedball Art Products, LLC	Emergency Telephone Number 704-838-1475
Address (Number, Street, City, State, and ZIP Code) 2226 Speedball Road Statesville, NC 28677 USA	Telephone Number for Information 704-838-1475
Date Prepared: March 1, 2004	Signature of Preparer (optional)

#### Section II – Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s)):	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(optional)
Mineral Spirits (CAS #8052-41-3)	N/A	500рр	N/A	3.5-9.9%
Den de et labaling conformer to ASTM D 4326 American d fou the		the Aut P Cueff	Madaniala Taratita	4. I

Product labeling conforms to ASTM D-4236. Approved for the AP seal as per the Art & Craft Materials Institute, Inc. (ACMI). Note: This product has been certified to be non-toxic. This product has been evaluated by a Toxicologist only as per intended usage. DO NOT DEVIATE FROM INTENDED USE.

#### Section III - Physical/Chemical Characteristics

Boiling Point	275°F-410°F	Specific Gravity ( $H_2O = 1$ )	.96-1.62
Vapor Pressure (mm Hg.)	Unknown	Melting Point	N/A
Vapor Density (AIR = 1)	Greater than 1	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water	Not soluble	Appearance and Odor	Paste with slight odor

#### Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) Greater than 105°F TCC	Flammable Limits <b>N/A</b>	LEL N/A	UEL N/A
Extinguishing Media Water spray, dry chemical, foam & carbor	1 dioxide		
Special Fire Fighting Procedures			
Wear self-contained breathing apparatus ( gear. Use water to keep fire-exposed contai		d or equivalent) and	d full protective
Wear self-contained breathing apparatus (	iners cool.	- /	-

#### Section V - Reactivity Data

Stability	Unstable	Stable	Conditions to Avoid None known.
Incompatibility (M Avoid contact v	laterials to Avoid) with strong oxidi	zing agent	s
	position or Byprodu of combustion-c		noxide & carbon monoxide
Hazardous Polymerization	May Occur	Will Not Occur	Conditions to Avoid N/A

#### Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation? See below	Skin? Irritation with prolonged contact	Ingestion? N/A
	/	. Eye contact: can cause irritation and tr	ransient corneal injury.
Carcinogenicity: N/A	NTP? <b>N/A</b>	IARC Monographs? N/A	OSHA Regulated? N/A
Signs and Symptoms of Exp N/A	osure		
Medical Conditions General <b>Pre-existing skin, eye, a</b>	ly Aggravated by Exposure nd respiratory disorders.		
•		kin: wash affected area with soap & wat	er. Ingestion-do NOT

### Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled Large spills should be diked and absorbed on inert material such as sand.
Waste Disposal Method Incineration at permitted facility. Observe all Federal, State and local laws concerning health and environment.
Precautions to Be taken in Handling and Storing Treat as flammable material.
Other Precautions N/A

### **Section VIII - Control Measures**

Ventilation	Local Exhaust N/A	Special N/A		
	Mechanical (General) N/A	Other N/A		
Protective Gloves	Impervious		Eye Protection Safety Glasses or goggles	
Other Protective	Clothing or Equipment Eyewash fou	intains and saf	ety showers must be accessible.	
Work/Hygienic P	ractices Use protective cream who	ere excessive sl	kin contact is likely.	