

# Part of Thermo Fisher Scientific

# SAFETY DATA SHEET

Creation Date 01-Sep-2009 Revision Date 15-Aug-2016 Revision Number 2

1. Identification

Product Name 2-Propanol

Cat No.: A426F-1GAL; A426P-4; A426S-4; A426S-20; A426S-200

Synonyms 2-Propanol; IPA; Isopropyl alcohol; Propan-2-ol; Isopropanol

Recommended Use Laboratory chemicals.

Uses advised against No Information available

Details of the supplier of the safety data sheet

Company Emergency Telephone Number

Fisher Scientific CHEMTREC®, Inside the USA: 800-424-9300 One Reagent Lane CHEMTREC®, Outside the USA: 001-703-527-3887

Fair Lawn, NJ 07410 Tel: (201) 796-7100

# 2. Hazard(s) identification

## Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids

Serious Eye Damage/Eye Irritation

Category 2
Specific target organ toxicity (single exposure)

Category 3

Target Organs - Respiratory system, Central nervous system (CNS).

Specific target organ toxicity - (repeated exposure) Category 2

Target Organs - Kidney, Liver.

### **Label Elements**

## Signal Word

Danger

## **Hazard Statements**

Highly flammable liquid and vapor
Causes serious eye irritation
May cause respiratory irritation
May cause drowsiness or dizziness
May cause damage to organs through prolonged or repeated exposure

2-Propanol Revision Date 15-Aug-2016



## **Precautionary Statements**

#### Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

#### Response

Get medical attention/advice if you feel unwell

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

#### Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

#### **Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

#### Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

## Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

## Disposal

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

None identified

# 3. Composition / information on ingredients

Component	CAS-No	Weight %
Isopropyl alcohol	67-63-0	>95

## 4. First-aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Obtain medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if

symptoms occur.

**Inhalation** Move to fresh air. Obtain medical attention. If not breathing, give artificial respiration.

**Ingestion** Do not induce vomiting. Obtain medical attention.

2-Propanol

Most important symptoms/effects

Breathing difficulties. May cause central nervous system depression: Inhalation of high

vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea

and vomiting

Treat symptomatically **Notes to Physician** 

## Fire-fighting measures

CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam. Cool closed containers exposed to fire **Suitable Extinguishing Media** 

with water spray.

**Unsuitable Extinguishing Media** Water may be ineffective

Flash Point 12 °C / 53.6 °F

Abel Closed Cup (BS 2000 Part 170, IP 170, AS/NZS 2106) Method -

**Autoignition Temperature** 

**Explosion Limits** 

425 °C / 797 °F

12 vol % Upper Lower 2 vol %

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

#### Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

#### **Hazardous Combustion Products**

Carbon monoxide (CO) Carbon dioxide (CO2) peroxides

## **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

N	F	P	Α
---	---	---	---

Health	Flammability	Instability	Physical hazards
2	3	0	N/A

### Accidental release measures

**Personal Precautions** 

**Environmental Precautions** 

Use personal protective equipment. Remove all sources of ignition. Take precautionary measures against static discharges. Avoid contact with skin, eyes and clothing. Should not be released into the environment. See Section 12 for additional ecological

information.

Up

Methods for Containment and Clean Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. Keep in suitable, closed containers for disposal.

# 7. Handling and storage

Handling

Wear personal protective equipment. Keep away from open flames, hot surfaces and sources of ignition. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing. Do not breathe vapors or spray mist. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Keep away from heat and sources of ignition. Flammables area. Keep container tightly **Storage** 

closed in a dry and well-ventilated place.

# 8. Exposure controls / personal protection

#### **Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
Isopropyl alcohol	TWA: 200 ppm	(Vacated) TWA: 400 ppm	IDLH: 2000 ppm
	STEL: 400 ppm	(Vacated) TWA: 980 mg/m <sup>3</sup>	TWA: 400 ppm
		(Vacated) STEL: 500 ppm	TWA: 980 mg/m <sup>3</sup>
		(Vacated) STEL: 1225 mg/m <sup>3</sup>	STEL: 500 ppm
		TWA: 400 ppm	STEL: 1225 mg/m <sup>3</sup>
		TWA: 980 mg/m <sup>3</sup>	-

Component	Quebec	Mexico OEL (TWA)	Ontario TWAEV
Isopropyl alcohol	TWA: 400 ppm	TWA: 400 ppm	TWA: 200 ppm
	TWA: 985 mg/m <sup>3</sup>	TWA: 980 mg/m <sup>3</sup>	STEL: 400 ppm
	STEL: 500 ppm	STEL: 500 ppm	
	STEL: 1230 mg/m <sup>3</sup>	STEL: 1225 mg/m <sup>3</sup>	

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

**Engineering Measures** Ensure that eyewash stations and safety showers are close to the workstation location. Use

explosion-proof electrical/ventilating/lighting/equipment. Ensure adequate ventilation,

especially in confined areas.

**Personal Protective Equipment** 

Wear appropriate protective eyeglasses or chemical safety goggles as described by **Eye/face Protection** 

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure.

No protective equipment is needed under normal use conditions. **Respiratory Protection** 

Handle in accordance with good industrial hygiene and safety practice. **Hygiene Measures** 

## 9. Physical and chemical properties

**Physical State** Liquid **Appearance** Colorless Alcohol-like Odor

No information available **Odor Threshold** 

7 1% aq. sol pН

**Melting Point/Range** -89.5 °C / -129.1 °F

**Boiling Point/Range** 81 - 83 °C / 177.8 - 181.4 °F @ 760 mmHg

**Flash Point** 12 °C / 53.6 °F

Abel Closed Cup (BS 2000 Part 170, IP 170, AS/NZS 2106) Method -

**Evaporation Rate** 1.7

Not applicable Flammability (solid,gas)

Flammability or explosive limits

**Decomposition Temperature** 

**Upper** 12 vol % 2 vol % Lower

43 mmHg @ 20 °C 2.1 @ 20 °C / 68 °F **Vapor Pressure Vapor Density** 

**Specific Gravity** 0.785

Solubility Miscible with water Partition coefficient; n-octanol/water No data available **Autoignition Temperature** 425 °C / 797 °F No information available

2.27 mPa.s at 20 °C **Viscosity** 

2-Propanol

Molecular FormulaC3 H8 OMolecular Weight60.1

**VOC Content(%)** 59.9 % (EC/1999/13)

Refractive index 1.377 at 20 °C / 68 °F (ASTM D-1218)

Surface tension 22.7 mN/m at 20 °C / 68 °F

Coefficient of expansion 0.0009 / °C

Dielectric constant 18.6 at 20 °C / 68 °F

Heat of vapourisation 665 J/g

**Specific heat capacity**3 kJ/kg °C at 20 °C / 68 °F **Thermal conductivity**3 kJ/kg °C at 20 °C / 68 °F

0.137 W/m °C at 20 °C / 68 °F

# 10. Stability and reactivity

Reactive Hazard None known, based on information available

**Stability** Stable under normal conditions.

Conditions to Avoid Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of

ignition.

Incompatible Materials Strong oxidizing agents, Acids, Halogens, Acid anhydrides

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), peroxides

Hazardous Polymerization Hazardous polymerization does not occur.

**Hazardous Reactions**None under normal processing.

# 11. Toxicological information

**Acute Toxicity** 

**Product Information** 

**Component Information** 

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	
Isopropyl alcohol	5840 mg/kg (Rat)	13900 mg/kg (Rat)	72.6 mg/L (Rat) 4 h	
		12870 mg/kg (Rabbit)		

**Toxicologically Synergistic** 

Products

No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

 Irritation
 Irritating to eyes and skin

 Sensitization
 No information available

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

	Component	CAS-No	IARC	NTP ACGIH		OSHA	Mexico
Ī	Isopropyl alcohol	67-63-0	Not listed				

Mutagenic Effects No information available

**Reproductive Effects** No information available.

**Developmental Effects** No information available.

**Teratogenicity** No information available.

**STOT - single exposure** Respiratory system Central nervous system (CNS)

STOT - repeated exposure Kidney Liver

**Aspiration hazard** No information available

2-Propanol

Symptoms / effects.both acute and May cause central nervous system depression; Inhalation of high vapor concentrations may

cause symptoms like headache, dizziness, tiredness, nausea and vomiting

**Endocrine Disruptor Information** No information available

**Other Adverse Effects** The toxicological properties have not been fully investigated.

# 12. Ecological information

### **Ecotoxicity**

delaved

. Do not empty into drains.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Isopropyl alcohol	EC50: > 1000 mg/L, 72h (Desmodesmus	LC50: > 1400000 µg/L, 96h (Lepomis macrochirus)	= 35390 mg/L EC50 Photobacterium	13299 mg/L EC50 = 48 h 9714 mg/L EC50 = 24 h
	subspicatus) EC50: > 1000 mg/L, 96h	LC50: = 11130 mg/L, 96h static (Pimephales	phosphoreum 5 min	
	(Desmodesmus subspicatus)	promelas) LC50: = 9640 mg/L, 96h		
	Subspicatus)	flow-through (Pimephales		
		promelas)		

Persistence and Degradability **Bioaccumulation/ Accumulation**  Persistence is unlikely based on information available.

No information available.

**Mobility** 

Will likely be mobile in the environment due to its volatility.

Component	log Pow		
Isopropyl alcohol	0.05		

## 13. Disposal considerations

**Waste Disposal Methods** 

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

## 14. Transport information

DOT

UN1219 **UN-No Proper Shipping Name** Isopropanol

**Hazard Class** 3 Ш **Packing Group** 

**TDG** 

**UN-No** UN1219

**Proper Shipping Name ISOPROPANOL** 

**Hazard Class Packing Group** Ш

<u>IATA</u>

**UN-No** UN1219 **Proper Shipping Name** Isopropanol

**Hazard Class Packing Group** Ш

IMDG/IMO

**UN-No** 

**Proper Shipping Name** Isopropanol (Isopropyl alcohol)

**Hazard Class Packing Group** 

# 15. Regulatory information

All of the components in the product are on the following Inventory lists: X = listed

2-Propanol

#### International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	<b>ENCS</b>	AICS	IECSC	KECL
Isopropyl alcohol	Х	Χ	-	200-661-7	-		Χ	Χ	Χ	Х	Х

## Legend:

- X Listed
- E Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.
- F Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.
- N Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.
- P Indicates a commenced PMN substance
- R Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.
- S Indicates a substance that is identified in a proposed or final Significant New Use Rule
- T Indicates a substance that is the subject of a Section 4 test rule under TSCA.
- XU Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).
- Y1 Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.
- Y2 Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

## **U.S. Federal Regulations**

TSCA 12(b) Not applicable

### **SARA 313**

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Isopropyl alcohol	67-63-0	>95	1.0

### SARA 311/312 Hazard Categories

Acute Health Hazard
Chronic Health Hazard
Fire Hazard
Sudden Release of Pressure Hazard
No
Reactive Hazard
No

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

**OSHA** Occupational Safety and Health Administration

Not applicable

#### **CERCLA**

Not applicable

California Proposition 65

This product does not contain any Proposition 65 chemicals

## U.S. State Right-to-Know

Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Isopropyl alcohol	X	X	X	=	Х

### **U.S. Department of Transportation**

Reportable Quantity (RQ): N
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

### **U.S. Department of Homeland Security**

This product does not contain any DHS chemicals.

2-Propanol Revision Date 15-Aug-2016

### Other International Regulations

Mexico - Grade Serious risk, Grade 3

#### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

WHMIS Hazard Class

B2 Flammable liquid
D2B Toxic materials



### 16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 01-Sep-2009

 Revision Date
 15-Aug-2016

 Print Date
 15-Aug-2016

**Revision Summary** This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS)

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**